



DTG-C

MODEL X

Ethernet port for LAN or open network printing

Proven industrial print head technology, Ricoh GH2220

AUTOMATIC platen height adjustment, just load your garment and hit print!

Easy access ink cartridge with precise value monitoring

7-inch full color display panel for total on-board control

USB memory port for PC-free printing

Quick change platen system for multiple platens. Small, medium, large, hat, sleeve, koozie, shoe, mask, etc.



MODELX

Auto platen height for easy
DTG AND DTF printing



HUGE 7-inch touch screen

MODEL X

Easy to use RIP software- Turbo RIP included

Textile color:

Printer

Printer	Resolution
Model X File	600 x 600 dpi - 8 pass
Platen	Ink drop size
Medium (12.6 x 18 in)	Large

 Print

Sizing & Positioning

Scale % Position , in

Size X in Center 

Apply Rotate 

Background

Image selection

Color tolerance

White Ink

Add white underbase Grayscale

Print white only Add white highlight

White Ink Settings

Resolution

White Ink Adjustments

Opacity -100

Choke 0

-100



MODELX

Model X Business in a Box!

Printer	\$18,950	\$15,950
Training	\$795	\$0
Small Platen	\$395	\$0
Medium Platen	\$495	\$0
Large Platen	\$495	\$0
Pretreat Sprayer and Pretreat Fluid	\$225	\$0
TurboRIP Software	\$665	\$0
Full set of ink	\$414	\$0
Cleaning fluid and supplies	\$235	\$0
Total	\$22,669	\$15,950
Total Savings	\$6719	



MODEL X

Printer Specifications

General specifications

Printable area	Up to 19.6" x 16" / 49.8cm x 40.6cm	Connectivity	USB drive and ethernet
Print head technology	Ricoh piezo-electric drop-on-demand inkjet	Electrical requirements	100/120VAC 50-60Hz, 0.65A max, 70 watts
Ink chambers/nozzles	4 Ricoh print heads (GH2220) 8 channels/192 nozzles per channel	Dimensions	18.9" H x 52.2" L x 33.9" W
Print speeds		Weight	242lbs (110kg)
10" x 8" graphic			
Light- speed	28 seconds		
Light- fine	42 seconds		
Resolution	600-1200 dpi		
Ink	Water based pigment ink		
Ink delivery system	Advanced closed-loop delivery with auto ink circulation		
Printable substrates	Cotton, cotton/poly blends, poly, DTF		
Table height adjustment	Automatic or manual		
Operating environment	59F/15C to 90F/32C 35-80% humidity		

MODELX