

Important Need to Knows.


1. **Always leave your printer on** to allow the machine to perform the necessary automatic maintenance. Any time white ink is loaded into the Model X the printer **MUST** run the auto maintenance to avoid clogs. If you would like to shut down your machine for more than 12 hours, it is recommended that you flush the white ink out of the system beforehand. Remember, if the printer cannot clean itself while white ink is loaded, the print head carriage warranty may be voided.
 -
1. **Do not run the printer dry.** The printer will stop performing the auto maintenance if any of the ink carts reads 0%. It is recommended you replace your ink carts at 5% to avoid the possibility of your machine running dry and stopping the auto maintenance cycle. Remember, if the printer cannot clean itself while white ink is loaded, the print head carriage warranty may be voided.
 -
1. **Perform daily and weekly maintenance.** Each **day** it is recommended that you run a nozzle check. This will help you understand how your print heads are firing and will help you to see potential issues before they become problems that can't be solved. Each **week**, if white ink is loaded, you **MUST** clean the heads and the maintenance station, **EVEN IF** you're not printing with the machine.

Get to know your printer

Front

Front Cover

Open the front cover for maintenance. Otherwise keep it closed.




Ink Cartridges
Access

Touch Panel

Platen

Place the T-shirt here.
A medium-sized platen is already
installed. Optional larger and smaller
platens are available.

Sub Power
It turns machine on/off




USB Port (2.0)


Back of the printer

1.2 Back

Normally leave it on. When the machine is not in use for a long period or when you move the machine, turn the main power switch off



Inside the printer



Carriage

Underneath there is the print head and the head nozzle. It moves left and right when printing. The carriage requires regular cleaning


Head Cap

It prevents the print head from drying out


Wiper

It is a gum plate that wipes the ink off on the print head

Installation



Open the front cover and remove bracket fix platen.




Connect waste ink bottle tube to valve on the right-back side of printer.


Installation (cont.)

3. Connect the power cable and turn on the AC power switch.


Power Connector



AC Power Switch




4. Insert ink cartridge.



Installation (cont)

5. Hold down the sub power button for more than 3 seconds.



- To turn the power on - hold down the sub power for more than 3 seconds.
- To turn the power off - hold down the sub power for more than 5 seconds.

CAUTION - Make sure that the main power switch and sub power are always turned on. If you do not, the ink in head could settle and/or coagulate, causing poor image quality or printer failure.

6. The printer is starting to boot up.

7. After booting up, the printer will perform initial charging if the printer is not already charged - initial charging takes about 20 minutes.

WARNING - During the initial ink charging, don't open cartridge cover or cut power.

8. Finishing initial charging, the printer shows "Ready".